

Unstable-Funcons-beta: Postponing *

The PLaNCompS Project

Postponing.cbs | PLAIN | PRETTY

Postponing

```
[ Entity  postponing
  Funcon  postpone
  Funcon  postpone-after-effect
  Funcon  after-effect ]
```

A funcon term can extend itself (e.g., with code to release the resources allocated to it) using general funcons for postponed execution. When a step from X to X' executes `postpone(Y)` (which computes `null`), the corresponding step of `postpone-after-effect(X)` gives `postpone-after-effect(after-effect(X', Y))`, so that normal termination of X' is followed by the effect of Y .

The control entity `postponing(A)` signals that the execution of the body of the abstraction A is postponed:

```
Entity  _  $\frac{\text{postponing}(\_ : (\text{abstractions}(\Rightarrow \text{null-type}))?)}{\_}$  _
```

The funcon `postpone(X)` forms a closure from X and signals that its execution is postponed:

```
Funcon  postpone(_ :  $\Rightarrow$  values) :  $\Rightarrow$  null-type

Rule     $\frac{\text{given-value}(V) \vdash \text{closure give}(V, X) \xrightarrow{\text{postponing}(\_)} A}{\text{given-value}(V) \vdash \text{postpone}(X) \xrightarrow{\text{postponing}(A)} \text{null-value}}$ 

Rule     $\frac{\text{given-value}(\_) \vdash \text{closure no-given } X \xrightarrow{\text{postponing}(\_)} A}{\text{given-value}(\_) \vdash \text{postpone}(X) \xrightarrow{\text{postponing}(A)} \text{null-value}}$ 
```

The funcon `postpone-after-effect(X)` handles each signal `postponing(A)` by adding it as an after-effect of X :

*Suggestions for improvement: plancomps@gmail.com.
Reports of issues: <https://github.com/plancomps/CBS-beta/issues>.

Funcon `postpone-after-effect`($_ : \Rightarrow T$) : $\Rightarrow T$

Rule
$$\frac{X \xrightarrow{\text{postponing}(\)} X'}{\text{postpone-after-effect}(X) \xrightarrow{\text{postponing}(\)} \text{postpone-after-effect}(X')}$$

Rule
$$\frac{\begin{array}{c} X \xrightarrow{\text{postponing}(A)} X' \\ A \rightsquigarrow \text{abstraction } Y \end{array}}{\text{postpone-after-effect}(X) \xrightarrow{\text{postponing}(\)} \text{postpone-after-effect}(\text{after-effect}(X', Y))}$$

Rule `postpone-after-effect`($V : \text{values}$) $\rightsquigarrow V$

The funcon `after-effect`(X, Y) first executes X . If X computes a value V , it then executes Y , and computes V :

Funcon `after-effect`($X : \Rightarrow T, Y : \Rightarrow \text{null-type}$) : $\Rightarrow T$
 $\rightsquigarrow \text{give}(X, \text{sequential}(Y, \text{given}))$